

HEAVY-DUTY INDUSTRIAL SCALE REMOVER

Heavy-Duty Industrial Scale Remover is ideal for use on boilers, piping systems, evaporating equipment, hot water heating systems, HVAC and solar systems. Powerful and safer to use on equipment in refineries, foundries, paper mills, chemical plants, food processing plants, water treating facilities, and more.



FOR BEST RESULTS



SATURATE

Apply generously and allow to saturate area to be cleaned.



ACTIVATE

Allow to penetrate up to 20 minutes or longer as needed.



AGITATE

Scrub lightly with brush or cloth as needed.



RINSE

Rinse. Repeated applications may be required for heavy build-ups.

FEATURES

- Does not oxidize, corrode or attack metals
- Eliminates pressure washing and mechanical removal
- Natural and biodegradable
- Contains no Hydrochloric, Phosphoric, Muriatic, or Citric acids
- No VOCs, petroleum products, or carcinogens





HEAVY-DUTY INDUSTRIAL SCALE REMOVER

AVAILABLE ITEMS

PAKI NU.	DESCRIPTION
R043-41	1 Gallon (3.78L) Bottle – Case of 4
R043-05	5 Gallon (18.93L) Pail
R043-15	15 Gallon (56.78L) Drum
R043-55	55 Gallon (208.2L) Drum
R043-27	275 Gallon (1041L) Tote
R043-12	32oz (946mL) Ready-To-Use Bottle – Case of 12
R043-32	Empty 32oz (946mL) Bottle — Case of 12

ACAIA.
The Nature of Innovation

Please recycle packaging.

(800) 99-AGAIA | Sales

(800) 71-AGAIA | Service & Support (954) 366-7200 | Corporate Office

PRODUCT SPECIFICATIONS

Description	Ready-To-Use (RTU)
Appearance:	Water-like Liqiud
Color:	Clear to Amber
Odor:	Slightly Acrid
pH:	2.4
Melting Point/Freezing Point:	5°C (41°F)
Boiling Point:	112°C (233.6°F))
Flash Point:	200°C (392°F)
Solubility:	100%
Specific Gravity:	1.16 g/mL
Specific Gravity:	1.056

GHS CLASSIFICATION



HAZARDS:

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

PRECAUTIONS:

P264 - Wash exposed skin thoroughly after handling.

P280 - Wear eye protection, protective gloves.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

P501 - Please dispose of excess or unused product in accordance with local, state or national legislation.

CONTAINS:

Lactic Acid (CASRN 50-21-5)

NOT RECOMMENDED FOR USE ON:

Granite, Polished Stone, Concrete or other High-Calcium Surfaces.

Manufactured for Agaia, Inc. • Made in the USA

U.S. Pat. 8,859,483 & 8,455,426 | © 2016 Agaia, Inc. All Rights Reserved.

All information, representations, product images and claims may be subject to change by Agaia, Inc. without notice. For questions concerning our products, specification, or utilization please refer to a qualified expert of Evolve products or the latest MSDS.